

Alumina Bi-Fold Survey Sheet

Please complete and email all sheets to
sales@pearlwindows.co.uk or send by fax on **01942 843587**



Fabricator Details Contact

Linair Fabricator: Yes ☐ No ☐

Company Name:	Todays Date:	Preferred Delivery Date:
----------------------	---------------------	---------------------------------

Alumina Bi-Fold doors are supplied as unglazed products. All fabricated doors will be delivered to the fabricator's normal profile delivery address.

Contact Name:	Tel:
----------------------	-------------

Email:	Fax:
---------------	-------------

Fabricator Job Reference

Job Reference:	Covering P/O Number:
-----------------------	-----------------------------

Opening Configuration

Width (mm) = 610 - 1300 Height (mm) = 1960 - 2600 110 L ☐ Width (mm) = 1580 - 2450 Height (mm) = 1960 - 2600	Width (mm) = 610 - 1300 Height (mm) = 1960 - 2600 110 R ☐ Width (mm) = 1635 - 3720 Height (mm) = 1960 - 2600	Width (mm) = 1120 - 2510 Height (mm) = 1960 - 2600 211 ☐ Width (mm) = 1635 - 3720 Height (mm) = 1960 - 2600	Width (mm) = 1635 - 3720 Height (mm) = 1960 - 2600 220 L ☐ Width (mm) = 1635 - 3720 Height (mm) = 1960 - 2600	Note: All doors are viewed from outside. Please tick the box of the opening configuration required. One door style only per order form.	
Width (mm) = 2145 - 4930 431 R ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3010 - 4730 Height (mm) = 1960 - 2600 321 L ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3010 - 4730 Height (mm) = 1960 - 2600 321 R ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3060 - 4820 Height (mm) = 1960 - 2600 330 L ☐ Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600	Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600 330 R ☐ Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600	Width (mm) = 2145 - 4930 Height (mm) = 1960 - 2600 431 L ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600
Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600 440 L ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600 440 R ☐ Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600 422 ☐ Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600	Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600 541 L ☐ Width (mm) = 3175 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 2720 - 5920 Height (mm) = 1960 - 2600 541 R ☐ Width (mm) = 3175 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 2660 - 6000 Height (mm) = 1960 - 2600 550 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600
Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 550 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 532 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 532 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 651 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 651 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 660 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600
Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 660 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 633 ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 761 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 761 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 770 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 770 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600
Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 743 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 743 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 752 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 752 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 743 L ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600	Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600 743 R ☐ Width (mm) = 3170 - 6000 Height (mm) = 1960 - 2600

All opening configuration drawings are drawn for illustration purposes only to give a representation of how the door styles would operate.

Door Specification

Finished Product Size:

Width:

Height:

Note: all sizes include add-ons, cills & thresholds.
MIN and MAX overall frame sizes shown above
each configuration.

Drainage Type: Concealed ☐ Face ☐

Tip: Liniar recommends concealed drainage
when possible.

Trickle Vent: Yes ☐ No ☐

Note: trickle vents to each alternating sash
would be standard practice.

Glazing Bead (Unglazed only):

28mm ☐ 36mm ☐ 40mm ☐

Note: 36mm & 40mm beads are only
available on internally foiled doors.

Add-Ons & Head Vents:

PVCu

10 mm

20 mm

50 mm

HV

Top

Bottom

Left

Right

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

Note: HV option denotes 'Head Vent'. Only available
on doors which are foiled on both faces.

Aluminium

10 mm

HV

Top

Left

Right

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

☐

Only available in the following colours:
White RAL Paint, Grey RAL Paint, 7016
Grey Foil, Rosewood Foil and Irish Oak Foil.
Note: Can be used as an Add-On or Head
Vent. Select only one for the Top part of
the Bi-Fold.

Opening Direction: Inwards ☐ Outwards ☐

Tip: check obstructions have been considered
when stating opening direction.

Door Restrictor: Yes ☐ No ☐

Note: restrictors to be used on single leaf doors
only. 1 per applicable sash e.g. 3-2-1, 4-3-1 etc.

Restricted Site Access: Yes ☐ No ☐

Note: outer frame will come
flat packed if 'Yes' is selected.

Optional PVCu Midrail:

Q. Midrail Required? Yes ☐ No ☐

Q. Letterbox Required? Yes ☐ No ☐

Note: All midrails positioned at 850mm from
bottom of frame 1 midrail per sash UOS, letterbox
(if applicable) positioned in master door UOS.
Note: Only available on doors which are foiled on
both faces.

Colour Specification

ALL internal & external foil finishes grained UOS.

Select Door Colour Required

External Foil		External RAL		Internal RAL		Internal Foil	
Colour	Closest RAL	Colour	Closest RAL	Colour	Closest RAL	Colour	Closest RAL

RAL Paint Only (Both Sides)

		External RAL		Internal RAL			
☐		White (Gloss)	9910	White (Gloss)	9910		
☐		Grey (Matt)	7016	Grey (Matt)	7016		
☐		Black (Matt)	9011	Black (Matt)	9011		
☐		Grey (Matt)	7016	White (Gloss)	9910		

Foiled on Both Faces

☐	Irish Oak	N/A				Irish Oak	N/A
☐	Golden Oak	N/A				Golden Oak	N/A
☐	Rosewood	N/A				Rosewood	N/A
☐	Grey	7016				Grey	7016
☐	Black Brown	8022				Black Brown	8022
☐	Cream	9001				Cream	9001
☐	White	9010				White	9010

Foiled (External Only) on White RAL Paint

☐	Cream	9001		White	9910		
☐	Chartwell Green	N/A		White	9910		
☐	Golden Oak	N/A		White	9910		
☐	Rosewood	N/A		White	9910		
☐	Grey	7016		White	9910		
☐	Black Brown	8022		White	9910		

Special Foil Colours Only, input colours as required. Combination availability TBC by Liniar

☐							
--------------------------	--	--	--	--	--	--	--

Hardware Colour:

White ☐ Black ☐ Chrome ☐ Gold ☐

Applies to the following products: BF050 (Roller),
MBF060 (Roller), ABF071 (Butt Hinge),
ABF072 (C Handle) and LBF041 (Magnets).

Handle Colour:

White ☐ Black ☐ Chrome ☐ Dark Chrome ☐ Gold ☐

Applies to the following products: MBF080 (Handle),
LBF081 (Slim Handle), LBF082 (Slim Handle) and
MBF042 (Escutcheon).

01942 843 586

sales@pearlwindows.co.uk

www.pearlwindows.co.uk

pearlTM
WINDOW SYSTEMS LTD

Special Requirements

Threshold Options:

